

SPECIFICATIONS



		Sector Lithium-Ion 15 kW	4 Seater Sector Lithium-Ion 15 kW	Sector Lithium-Ion 7.5 kW	Sector Lithium-Ion 5 kW
Motor	Type	AC Motor	AC Motor	AC Motor	AC Induction Motor
	Rated power	15 kW @ 6000 rpm	15 kW @ 6000 rpm	7.5 kW @ 6000 rpm	5 kW @ 6000 rpm
	Max power	37.5 kW	37.5 kW	19 kW	14 kW
	Max torque	168 Nm	168 Nm	140 Nm	123 Nm
	Battery capacity	16.5 kWh	16.5 kWh	14.7 kWh	12.7 kWh
	Charge time (hours)	5.5 dependent on depth of charge	5.5 dependent on depth of charge	5 dependent on depth of charge	4.5 dependent on depth of charge
Drive Train	Transmission ratio	H gear 11.28 : 1, L gear 22.12 : 1	H gear 11.1 : 1, L gear 22.2 : 1	14.14 : 1	14.14 : 1
	Drive system	2WD or 4WD	2WD or 4WD	2WD or 4WD	2WD or 4WD
	Differential lock	Electric control : switch	Electric control : switch	Electric control : switch	Electric control : switch
	Gear selection	F-N-R with H-M-L	F-N-R with H-M-L	F-N-R with H-M-L	F-N-R with H-M-L
Brakes Steering Suspension	Front / rear brakes	Hydraulic disc	Hydraulic disc	Hydraulic disc	Hydraulic disc
	Parking brake	Axis brake, pedal-breaking	Axis brake, pedal-breaking	Axis brake, pedal-breaking	Axis brake, pedal-breaking
	Steering	Electronic power steering	Electronic power steering	Electronic power steering	Mechanical
	Suspension front / rear	Independent, dual A-arm type	Independent, dual A-arm type	Independent, dual A-arm type	Independent, dual A-arm type
Dimensions	Length x width x height	3010 mm x 1585 mm x 2020 mm	3810 mm x 1585 mm x 2020 mm	3010 mm x 1585 mm x 2020 mm	2800 mm x 1615 mm x 1850 mm
	Wheelbase	1950 mm	2755 mm	1950 mm	1850 mm
	Ground clearance front / rear	310 mm / 310 mm	310 mm / 310 mm	310 mm / 310 mm	280 mm / 240 mm
	Turning diameter	8.6 m	8.6 m	8.6 m	6.84 m
	Front tyre	27 x 9-14 6PR	26 x 9-14 6PR	27 x 9-14 6PR	26 x 9-14 6PR
	Rear tyre	27 x 11-14 6PR	26 x 11-14 6PR	27 x 11-14 6PR	26 x 11-14 6PR
Weight	Weight	820 kg / 1808 lbs	921 kg / 2030 lbs	778 kg / 1715 lbs	704 kg / 1522 lbs
	Towing capacity	350 kg / 772 lbs	350 kg / 772 lbs	350 kg / 772 lbs	225 kg / 496 lbs
Cargo Bed	Width	1430 mm	1430 mm	1430 mm	975 mm
	Length	1060 mm	1060 mm	1060 mm	760 mm
	Depth	330 mm	330 mm	330 mm	333 mm
	Volume	0.5 m ³	0.5 m ³	0.5 m ³	0.23 m ³
	Unloaded bed height	860 mm	860 mm	860 mm	780 mm
Capacity	227 kg / 500 lbs	227 kg / 500 lbs	227 kg / 500 lbs	227 kg / 500 lbs	